



STANDARD DETAILS

CITY OF SHERWOOD
ARKANSAS

TITLE

WOOD FENCE DETAIL
(WITH METAL POST)

Issue Date

January, 2007

STD-58

Revision Date

NOTES:

- *ALL FASTENING HARDWARE TO BE NON-CORROSIVE
- *CONTRACTOR SHALL USE 8p. GALVANIZED SIDING NAILS OR 2" GALVANIZED SCREWS THROUGHOUT.
- *ALL WOOD MEMBERS SHALL BE TREATED.

ROUND HEAD SHEET METAL
BLUNT POINT HARDENED
SELF TAPPING 20 GA.#10.

2 HOLE ELECTRICAL
METALLIC CONDUIT
STRAP 2" WIDE

5/8"x1 1/2"
LAG BOLTS
(EACH SIDE)

GALVANIZED 2 7/8" O.D.
SCH. 40 ASTM A53
GRADE 8 METAL POSTS
MAXIMUM 8' O.C.

8'-0" TYP. O.C.
METAL POST

PLAN VIEW

1"x6" TREATED
FACE BOARDS

2"x4" INTERMEDIATE
RAIL

2"x4" INTERMEDIATE
RAIL (TYP.)

METAL POST

2"x4" INTERMEDIATE
RAIL

1"x6" FACE BOARDS

2"x4" INTERMEDIATE
RAIL

4"

2" CLEAR

12"Ø CONC. FTG.
3000 PSI CONC
(TYP. ALL POSTS)

ELEVATION

N.T.S.